



LIGH-T_{v3}

COMPACT TETHERING STATION

Ruggedized and lightweight tethering station offering unlimited endurance to drone operators, for continuous aerial observation missions.



Used by major global industries in over 30 countries - Ask our team for references.

TRAFFIC MONITORING

EVENT COVERAGE

CROWD-CONTROL

SITUATIONAL AWARENESS

COMPATIBLE WITH OVER 20 COMMERCIAL DRONES



DJI Matrice 200



DJI Inspire 2



DJI Inspire 1



Acore Zoe



Yuneec H920



DJI M100

PORTABLE CONTINUOUS POWER



60m

Lightweight,
«Plug & Fly»



1.2 kW

Unlimited and secured
power



200 Mbs

Fast data transfer
Full Motion Video



Secured and
unjammable
communications



T-monitor
Smart warning
function



Multi-drone
compatible:
Inspire, Matrice, etc.



TECHNICAL SPECIFICATIONS



Characteristics	Data
Length	60 m
Micro-tether weight	10.5 g/m
Output voltage	6S or 12S
Power (output)	Up to 2500W (peak)
Safety Switch (onboard)	Included
Power input	220 - 250 VAC, 50 - 60 Hz
Data speed	200 Mb/s
Tensile strength	150 daN
Built-in protection	Electronic crowbar / Circuit-breaker
Tether Management System	Compact vertical reel
Total weight	12 kg
Dimensions	475 mm x 415 mm x 211 mm